




Features	TK-3230DX		TK-3230		CLS1410/1110
	BRS(Radio only)	LMR(FPU use)	BRS(Radio only)	LMR(FPU use)	BRS(Radio only)
Design					
Size(W,H,D) w/o projection	52 x 103.5 x 29.6 mm (incl.Ant:155.5 mm)		52 x 103.5 x 28.7 mm (incl.Ant:155.5 mm)		51 x 129 x 27 mm (incl.Ant)
Weight w/Battery	155 g w/Li-Ion (KNB-46L)		155 g w/Li-Ion (KNB-46L)		153 g w/Li-Ion
Output Power	1.5 W / 0.5 W (ERP)		1.5 W / 0.5 W (ERP)		1 W / 0.5 W (ERP)
LCD	4 digits/ 7segments + icon		4 digits/ 7segments + icon		1 digit/ 7segments + icon
Channel	6ch, 16ch	16ch	6ch, 16ch	16ch	2ch, 4ch
VOX	yes	yes	yes	yes	yes (1410 only)
Scrambler	yes	yes	yes	yes	-
Scan	yes	yes	yes	yes	yes (1410 only)
Call tone	yes(1-10)	yes(1-10)	yes(1-10)	yes(1-10)	yes(1-3)
Selectable Power On Tone	yes	yes	-	-	-
Companer	yes	yes	yes	yes	-
Selectable Mic sense	yes (High/ Normal)	yes (High/ Nomal)	yes(High/ Normal)	yes(High/ Normal)	yes (H/ M/ L)
Vibration	-	-	-	-	yes (1410 only)
Clone	Wireless	Wireless	Wireless	Wireless	yes(CHG required)
QT/DQT	QT 45/ DQT 174+off	QT/ DQT (incl.invert)	QT 39/ DQT 83+off	QT/ DQT(incl.invert)	QT39/ DQT83+off
FleetSync	PTT ID, ID display SELCALL, ID list =32	PTT ID, ID display SELCALL, ID list =32	PTT ID, ID display SELCALL, ID list =32	PTT ID, ID display SELCALL, ID list =32	-
Frequency Range	Preset 99ch	450-470 MHz	Preset 56ch	460-470MHz	Preset 56ch
Battery Life	14-hour/18-hour (Battery Saver Off/On)		14-hour/18-hour (Battery Saver Off/On)		12-hour, (10h w/3AA)
MIL	8 items (refer to MIL chart)		8 items (refer to MIL chart)		-
Dust & Water Protection	IP52		JIS2		-